Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method, comprising:
sharing control of a Bluetooth communications module between a primary processor system
and a secondary processor system, wherein sharing control comprises:

routing Bluetooth communications between the primary processor system and the

Bluetooth communications module via a sharing module; and

routing Bluetooth communications between the secondary processor system and the Bluetooth communications module via the sharing module:

wherein the sharing module does not modify software running on the primary processor system.

- 2. (Canceled)
- 3. (Currently Amended) The method of claim [[2]] 1, wherein sharing control further comprises:

presenting the Bluetooth communications module as a slave device; and presenting the primary processor system and secondary processor system as master devices to the Bluetooth communications module.

- 4. (Currently Amended) The method of claim [[2]] 1, wherein sharing control further comprises selecting whether to service Bluetooth communications either of the primary processor system or the secondary processor system.
- 5. (Currently Amended) The method of claim [[2]] 1, wherein sharing control further comprises:

converting all Bluetooth packets between a first transport mode and a second transport mode.

6. (Original) The method of claim 5, wherein the first transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI; and

wherein the second transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI.

- 7. (Original) The method of claim 1, wherein the communications module, the primary processor system and the secondary processor system are included in a notebook computer.
- 8. (Original) The method of claim 6, wherein the sharing module is integrated into the secondary processor system; and

wherein the secondary processor system is a low-power computer system and the primary processor system is a main CPU/OS computer system.

9. (Original) The method of claim 6, wherein the sharing module is integrated into the secondary processor system, and the secondary processor system is a multi-function Bluetooth enabled device; and

wherein the primary processor system includes a notebook, a tablet, a laptop, and a desktop computer system.

- 10. (Original) The method of claim 9, wherein the sharing module is integrated with a secondary controller of the secondary processor system.
- 11. (Original) The method of claim 6, wherein the sharing module is included in the primary processor system.
- 12. (Original) The method of claim 1, wherein the Bluetooth module communicates with one or more secondary Bluetooth devices.
- 13. (Currently Amended) The method of claim [[2]] 1, wherein the sharing module communicates with a USB host controller and a Bluetooth controller.

14. (Original) The method of claim 1, further comprising switching control between the primary processor system and secondary processor system, upon the occurrence of an event, wherein the event includes opening of a computer lid, receiving a data message by the first processor system, receiving a data message by the second processor system, closing a computer lid, and receiving a switch command.

15. (Currently Amended) A system, comprising:

means for sharing control of a Bluetooth communications module between a primary processor system and a secondary processor system having means for routing Bluetooth communications between the primary processor system and the Bluetooth communications module via a sharing module and means for routing Bluetooth communications between the secondary processor system and the Bluetooth communications module via the sharing module, wherein the sharing module does not modify software running on the primary processor system.

16. (Canceled)

17. (Currently Amended) The system of claim [[16]] 15, wherein sharing control further comprises:

means for presenting the Bluetooth communications module as a slave device; and means for presenting the primary processor system and secondary processor system as master devices to the Bluetooth communications module.

- 18. (Currently Amended) The system of claim [[16]] 15, wherein sharing control further comprises means for selecting whether to service either Bluetooth communications of the primary processor system or the secondary processor system.
- 19. (Currently Amended) The system of claim [[16]] 15, wherein sharing control further comprises:

means for converting Bluetooth data packets between a first transport mode and a second transport mode.

20. (Original) The system of claim 19, wherein the first transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI; and

wherein the second transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI.

- 21. (Original) The system of claim 15, wherein the communications module, the primary processor system and the secondary processor system are included in a notebook computer.
- 22. (Original) The system of claim 20, wherein the sharing module is integrated into the secondary processor system; and

wherein the secondary processor system is a low-power computer system and the primary processor system is a main CPU/OS computer system.

23. (Original) The system of claim 20, wherein the sharing module is integrated into the secondary processor system, and the secondary processor system is a multi-function Bluetooth enabled device; and

wherein the primary processor system includes a notebook, a tablet, a laptop, and a desktop computer system.

- 24. (Original) The system of claim 23, wherein the sharing module is integrated with a secondary controller of the secondary processor system.
- 25. (Original) The system of claim 20, wherein the sharing module is included in the primary processor system.
- 26. (Original) The system of claim 15, wherein the Bluetooth module communicates with one or more secondary Bluetooth devices.
- 27. (Currently Amended) The system of claim [[16]] 15, wherein the sharing module communicates with a USB host controller and a Bluetooth controller.

- 28. (Original) The system of claim 15, further comprising means for switching control between the primary processor system and secondary processor system, upon the occurrence of an event, wherein the event includes opening of a computer lid, receiving a data message by the first processor system, receiving a data message by the second processor system, closing a computer lid, and receiving a switch command.
- 29. (Currently Amended) A computer-readable medium having stored thereon a plurality of instructions, said plurality of instructions when executed by a computer, cause said computer to perform:

sharing control of a Bluetooth communications module between a primary processor system and a secondary processor system;

routing Bluetooth communications between the primary processor system and the Bluetooth communications module via a sharing module; and

routing Bluetooth communications between the secondary processor system and the Bluetooth communications module via the sharing module;

wherein the sharing module does not modify software running on the primary processor system.

30. (Canceled)

31. (Currently Amended) The computer-readable medium of claim [[30]] 29, having stored thereon additional instructions, said additional instructions when executed by a computer, cause said computer to further perform:

presenting the Bluetooth communications module as a slave device; and presenting the primary processor system and secondary processor system as master devices to the Bluetooth communications module.

- 32. (Currently Amended) The computer-readable medium of claim [[30]] 29, having stored thereon additional instructions, said additional instructions when executed by a computer, cause said computer to further perform selecting whether to service either Bluetooth communications of the primary processor system or the secondary processor system.
- 33. (Original) The computer-readable medium of claim [[30]] 29, having stored thereon additional instructions, said additional instructions when executed by a computer, cause said computer to further perform converting Bluetooth data packets between a first transport mode and a second transport mode.
- 34. (Original) The computer-readable medium of claim 33, wherein the first transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI; and

wherein the second transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI.

- 35. (Currently Amended) The computer-readable medium of claim [[35]] 29, wherein the communications module, the primary processor system and the secondary processor system are included in a notebook computer.
- 36. (Original) The computer-readable medium of claim 34, wherein the sharing module is integrated into the secondary processor system; and

wherein the secondary processor system is a low-power computer system and the primary processor system is a main CPU/OS computer system.

37. (Original) The computer-readable medium of claim 34, wherein the sharing module is integrated into the secondary processor system, and the secondary processor system is a multi-function Bluetooth enabled device; and

wherein the primary processor system includes a notebook, a tablet, a laptop, and a desktop computer system.

38. (Original) The computer-readable medium of claim 37, wherein the sharing module is integrated with a secondary controller of the secondary processor system.

- 39. (Original) The computer-readable medium of claim 34, wherein the sharing module is included in the primary processor system.
- 40. (Original) The computer-readable medium of claim 29, wherein the Bluetooth module communicates with one or more secondary Bluetooth devices.
- 41. (Currently Amended) The computer-readable medium of claim [[30]] 29, wherein the sharing module communicates with a USB host controller and a Bluetooth controller.
- 42. (Original) The computer-readable medium of claim 29, having stored thereon additional instructions, said additional instructions when executed by a computer, cause said computer to further perform switching control between the primary processor system and secondary processor system, upon the occurrence of an event, wherein the event includes opening of a computer lid, receiving a data message by the first processor system, receiving a data message by the second processor system, closing a computer lid, and receiving a switch command.
 - 43. (Currently Amended) A apparatus, comprising:
 - a Bluetooth sharing module;
 - a Bluetooth communications module connected to the Bluetooth sharing module;
 - a primary processor system connected to the Bluetooth sharing module; and

wherein the Bluetooth sharing module is configured to allow the primary processor system and secondary processor system to share control of the Bluetooth communications module via a host controller of the Bluetooth communications module, further wherein the sharing module routes Bluetooth communications between the primary processor system and the Bluetooth communications module via a sharing module, routes Bluetooth communications between the secondary processor system and the Bluetooth communications

module via the sharing module and does not modify software running on the primary

a secondary processor system connected to the Bluetooth sharing module,

44. (Canceled)

processor system.

45. (Currently Amended) The apparatus of claim [[44]] 43, wherein the sharing module

presents the Bluetooth communications module as a slave device; and presents the primary processor system and secondary processor system as master devices to the Bluetooth communications module.

46. (Currently Amended) The apparatus of claim [[44]] 43, wherein the sharing module selects whether to service Bluetooth communications either of the primary processor system or the secondary processor system.

- 47. (Currently Amended) The apparatus of claim [[44]] 43, wherein the sharing module converts all Bluetooth packets between a first transport mode and a second transport mode.
- 48. (Original) The apparatus of claim 47, wherein the first transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI; and wherein the second transport mode includes a universal serial bus (USB), an RS-232 connection, Firewire, and mPCI.
- 49. (Original) The apparatus of claim 43, wherein the sharing module, the primary processor system and the secondary processor system are included in a notebook computer.
- 50. (Original) The apparatus of claim 48, wherein the sharing module is integrated into the secondary processor system; and

wherein the secondary processor system is a low-power computer system and the primary processor system is a main CPU/OS computer system.

51. (Original) The apparatus of claim 48, wherein the sharing module is integrated into the secondary processor system, and the secondary processor system is a multi-function Bluetooth enabled device; and

wherein the primary processor system includes a notebook, a tablet, a laptop, and a desktop computer system.

- 52. (Original) The apparatus of claim 51, wherein the sharing module is integrated with a secondary controller of the secondary processor system.
- 53. (Original) The apparatus of claim 48, wherein the sharing module is included in the primary processor system.
- 54. (Original) The apparatus of claim 43, wherein the Bluetooth module communicates with one or more secondary Bluetooth devices.
- 55. (Currently Amended) The apparatus of claim [[44]] 43, wherein the sharing module communicates with a USB host controller and a Bluetooth controller.
- 56. (Original) The apparatus of claim 43, wherein the sharing module switches control of the Bluetooth controller between the primary processor system and secondary processor system, upon the occurrence of an event, wherein the event includes opening of a computer lid, receiving a data message by the first processor system, receiving a data message by the second processor system, closing a computer lid, and receiving a switch command.